TWB Gage Signal File to RSS SPS File Converter Analysis run date: 01 Dec 2013 00:10:20 Local

Analysis complete: 01 Dec 2013 01:29:27 Local

**Data Conversion Analysis Report** 

Duration of observation: 62.72 real-time seconds

Observation start time: 30 Nov 2013 06:03:00 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\2013-11-30\_002\_CH01\Folder.00001

Number of digitized input files: 160

First input filename: AS\_CH01-001.sig

Last input filename: AS\_CH01-160.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent FFT bins: 2048 FFT sweep time: 204.8  $\mu$ s

FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 160 input files, including padding: 305920 FFT BW: 5 MHz

FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz ( FFT bin # 574 ) FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero:  $9.35425 \mu W$  (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100  $\mu$ W DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20131130630.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second

SPS file start time: 30 Nov 2013 06:03:00.000 UTC SPS file end time: 30 Nov 2013 06:04:02.652 UTC