TWB Gage Signal File to RSS SPS File Converter Analysis run date: 01 Dec 2013 16:43:34 Local Analysis complete: 01 Dec 2013 18:02:20 Local

Data Conversion Analysis Report

Duration of observation: 62.72 real-time seconds

Observation start time: 30 Nov 2013 06:38:00 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\2013-11-30_010_CH01\Folder.00001

Number of digitized input files: 160

First input filename: AS_CH01-001.sig Last input filename: AS_CH01-160.sig

FFT sweeps per digitized data burst: 1023

Total FFT bins exported to SPS file: 411

DC offset applied to FFT before calculating dBm: 100 μ W DC offset applied to FFT after calculating dBm: 11 dBm

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 160 input files, including padding: 305920

FFT sweeps per digitized data burst including dead time padding: 1912

Digitized burst file size: 2096961 samples per file

FFT bins: 2048 FFT sweep time: 204.8 μ s

FFT BW: 5 MHz

SPS file detector sensitivity: 50 ADC counts per dB

Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984)

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

DC offset per FFT element zero: 10.0476 μ W (last FFT sweep of last data file)

- SPS output file name: AJ4CO-TWB-201311306380.sps
- SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Nov 2013 06:38:00.000 UTC
 - SPS file end time: 30 Nov 2013 06:39:02.652 UTC