## TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 01 Dec 2013 21:36:23 Local Analysis complete: 01 Dec 2013 22:56:26 Local

## **Data Conversion Analysis Report**

Observation start time: 30 Nov 2013 06:44:00 UTC Duration of observation: 62.72 real-time seconds

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\2013-11-30\_013\_CH01\Folder.00001 Number of digitized input files: 160 First input filename: AS\_CH01-001.sig Last input filename: AS\_CH01-160.sig

> Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53.4939 percent

> > FFT bins: 2048

FFT sweep time: 204.8 μs FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 160 input files, including padding: 305920

> FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984) Total FFT bins exported to SPS file: 411

 $\begin{array}{l} \mbox{DC offset per FFT element zero: 8.54073 $\mu$W$ (last FFT sweep of last data file) \\ \mbox{DC offset applied to FFT before calculating dBm: 100 $\mu$W$ \\ \mbox{DC offset applied to FFT after calculating dBm: 11 dBm$ \\ \mbox{SPS file detector sensitivity: 50 ADC counts per dB} \\ \mbox{DC offset applied to SPS data before export to SPS file: 1000 ADC counts} \end{array}$ 

SPS output file name: AJ4CO–TWB–201311306440.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Nov 2013 06:44:00.000 UTC SPS file end time: 30 Nov 2013 06:45:02.652 UTC