## TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 07 Dec 2013 10:15:53 Local Analysis complete: 07 Dec 2013 11:35:03 Local

## **Data Conversion Analysis Report**

Duration of observation: 59,976 real-time seconds

Observation start time: 07 Dec 2013 07:40:54 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131207 Io-B\2013-12-07\_02\_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS\_CH01-001.sig

Last input filename: AS\_CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT bins: 2048

FFT sweep time: 204.8  $\mu$ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912

Total FFT sweeps for 153 input files, including padding: 292536 FFT BW: 5 MHz

FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 13.0132  $\mu$ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100  $\mu$ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20131207074054.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 07 Dec 2013 07:40:54.999 UTC SPS file end time: 07 Dec 2013 07:41:54.911 UTC