TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 09 Dec 2013 17:31:39 Local Analysis complete: 09 Dec 2013 17:33:54 Local

Data Conversion Analysis Report

Observation start time: 09 Dec 2013 17:06:10 UTC Duration of observation: 1.96 real-time seconds

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131209 Test\2013-12-09 Test 6 - Wes's 21 MHz BPF at 35 dB down\Folder.00001 Number of digitized input files: 5 First input filename: AS CH01-1.sig Last input filename: AS CH01-5.sig Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53,4939 percent FFT bins: 2048 FFT sweep time: 204.8 μ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 5 input files, including padding: 9560 FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin \pm 984) Total FFT bins exported to SPS file: 411 DC offset per FFT element zero: 12.9537 μ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100 μ W DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO–TWB–20131209170610.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 09 Dec 2013 17:06:10.000 UTC SPS file end time: 09 Dec 2013 17:06:11.957 UTC