TWB Gage Signal File to RSS SPS File Converter Analysis run date: 15 Dec 2013 18:54:57 Local

Analysis complete: 15 Dec 2013 20:03:03 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real-time seconds

Observation start time: 15 Dec 2013 06:51:12 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131215 Io-A\2013-12-15_22_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS_CH01-001.sig

FFT sweeps per digitized data burst: 1023

Total FFT bins exported to SPS file: 411

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 153 input files, including padding: 292536

FFT sweeps per digitized data burst including dead time padding: 1912

Last input filename: AS_CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

> FFT bins: 2048 FFT sweep time: 204.8 μ s

> > FFT BW: 5 MHz

Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms

Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984)

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB

DC offset per FFT element zero: 14.3571 μ W (last FFT sweep of last data file)

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20131215065112.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 15 Dec 2013 06:51:12.000 UTC

SPS file end time: 15 Dec 2013 06:52:11.911 UTC