TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 17 Dec 2013 22:05:50 Local Analysis complete: 17 Dec 2013 23:14:45 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real-time seconds

Observation start time: 16 Dec 2013 08:09:07 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131216 Io-B\2013-12-16_08_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS_CH01-001.sig

Last input filename: AS_CH01-153.sig

Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms

Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 μ s FFT sweeps per digitized data burst: 1023

Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 5.81915 μ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20131216080907.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 16 Dec 2013 08:09:07.000 UTC SPS file end time: 16 Dec 2013 08:10:06.911 UTC