## TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 19 Dec 2013 01:32:23 Local Analysis complete: 19 Dec 2013 02:39:45 Local

## **Data Conversion Analysis Report**

Observation start time: 16 Dec 2013 08:26:02 UTC Duration of observation: 59.976 real-time seconds

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131216 Io-B\2013-12-16\_20\_CH01\Folder.00001 Number of digitized input files: 153 First input filename: AS\_CH01-001.sig Last input filename: AS\_CH01-153.sig

> Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 μs FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

> FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin ± 574 ) FFT display high frequency: 4.8 MHz (FFT bin ± 984 ) Total FFT bins exported to SPS file: 411

 $\begin{array}{c} \mbox{DC offset per FFT element zero: 5.60346 $\mu$W$ (last FFT sweep of last data file) } \\ \mbox{DC offset applied to FFT before calculating dBm: 100 $\mu$W$ } \\ \mbox{DC offset applied to FFT after calculating dBm: 11 dBm} \\ \mbox{SPS file detector sensitivity: 50 ADC counts per dB} \\ \mbox{DC offset applied to SPS data before export to SPS file: 1000 ADC counts} \end{array}$ 

SPS output file name: AJ4CO–TWB–20131216082602.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 16 Dec 2013 08:26:02.999 UTC SPS file end time: 16 Dec 2013 08:27:02.911 UTC