TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 29 Dec 2013 20:44:01 Local Analysis complete: 29 Dec 2013 21:51:03 Local

Data Conversion Analysis Report

Observation start time: 29 Dec 2013 08:45:51 UTC Duration of observation: 59.976 real-time seconds

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131229 Io-A-C\2013-12-29_05_CH01\Folder.00001 Number of digitized input files: 153 First input filename: AS_CH01-001.sig Last input filename: AS_CH01-153.sig

> Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 μs FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz

FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin \ddagger 574)

FFT display high frequency: 4.8 MHz (FFT bin \ddagger 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 5.53747 μ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO–TWB–20131229084551.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 29 Dec 2013 08:45:51.000 UTC SPS file end time: 29 Dec 2013 08:46:50.911 UTC