TWB Gage Signal File to RSS SPS File Converter Analysis run date: 30 Dec 2013 03:41:46 Local

Analysis complete: 30 Dec 2013 04:47:56 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real_time seconds

Observation start time: 29 Dec 2013 09:03:30 UTC

Data directory: R:\Observation Records\A14CO

FFT sweeps per digitized data burst: 1023

DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

Dead FFT sweeps between each digitized data burst: 889

Observatory\TWB\Gaqe\20131229 Io-A-C\2013-12-29 10 CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS CH01-001.sig

FFT bins: 2048

Last input filename: AS CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst cycle time: 392 ms

Digitized burst file duration: 209.696 ms

Dead time between data bursts: 182,304 ms. Digitization coverage: 53.4939 percent

FFT sweep time: 204.8 μ s

FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

SPS output file name: AJ4CO-TWB-20131229090330.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 29 Dec 2013 09:03:30.000 UTC SPS file end time: 29 Dec 2013 09:04:29.911 UTC

FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset per FFT element zero: 5.01105 μ W (last FFT sweep of last data file)