TWB Gage Signal File to RSS SPS File Converter Analysis run date: 08 Jan 2014 00:55:18 Local

Analysis complete: 08 Jan 2014 02:00:37 Local

## **Data Conversion Analysis Report**

Duration of observation: 59,976 real-time seconds

Observation start time: 30 Dec 2013 09:39:10 UTC

Data directory: R:\Observation Records\AJ4CO Observatory\TWB\Gage\20131230 Io-B\2013-12-30\_02\_CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS\_CH01-001.sig

Last input filename: AS\_CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8  $\mu$ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

DC offset per FFT element zero: 9.46202  $\mu$ W (last FFT sweep of last data file)

DC offset applied to FFT before calculating dBm: 100  $\mu$ W

Total FFT bins exported to SPS file: 411

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20131230093910.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second

SPS file start time: 30 Dec 2013 09:39:10.000 UTC SPS file end time: 30 Dec 2013 09:40:09.911 UTC