TWB Gage Signal File to RSS SPS File Converter Analysis run date: 26 Jan 2014 13:34:45 Local

Analysis complete: 26 Jan 2014 14:41:12 Local

**Data Conversion Analysis Report** 

Duration of observation: 59,976 real\_time seconds

Observation start time: 24 Jan 2014 05:11:39 LITC

Data directory: R:\Observation Records\A14CO

Observatory\TWB\Gage CS1220\20140124 Io-B\2014-01-24 01 CH01\Folder.00001

Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms.

FFT sweeps per digitized data burst: 1023

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 153 input files, including padding: 292536

Number of digitized input files: 153 First input filename: AS CH01-001.sig

Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8  $\mu$ s

Last input filename: AS CH01-153.sig

Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

DC offset per FFT element zero: 11.7209  $\mu$ W (last FFT sweep of last data file)

SPS file start time: 24 Jan 2014 05:11:39.000 UTC SPS file end time: 24 Jan 2014 05:12:38.911 UTC

FFT BW: 5 MHz FFT RBW: 4.88281 kHz

SPS file detector sensitivity: 50 ADC counts per dB

FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz ( FFT bin  $\sharp$  574 ) FFT display high frequency: 4.8 MHz (FFT bin # 984)

FFT sweeps per digitized data burst including dead time padding: 1912

Total FFT bins exported to SPS file: 411

SPS output file name: AJ4CO-TWB-20140124051139.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second

DC offset applied to FFT before calculating dBm: 100  $\mu$ W DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts