TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 31 Jan 2014 16:49:26 Local Analysis complete: 31 Jan 2014 17:55:31 Local

Data Conversion Analysis Report

Observation start time: 30 Jan 2014 05:11:52 UTC Duration of observation: 59.976 real-time seconds

Data directory: R:\Observation Records\A14CO Observatory\TWB\Gage CS1220\20140130 Io-A-C\2014-01-30 08 CH01\Folder.00001 Number of digitized input files: 153 First input filename: AS CH01-001.sig Last input filename: AS CH01-153.sig Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53,4939 percent FFT bins: 2048 FFT sweep time: 204.8 μ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin \pm 574) FFT display high frequency: 4.8 MHz (FFT bin \pm 984) Total FFT bins exported to SPS file: 411 DC offset per FFT element zero: 10.9314 μ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100 μ W DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB DC offset applied to SPS data before export to SPS file: 1000 ADC counts

> SPS output file name: AJ4CO–TWB–20140130051152.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Jan 2014 05:11:52.000 UTC SPS file end time: 30 Jan 2014 05:12:51.911 UTC