TWB Gage Signal File to RSS SPS File Converter Analysis run date: 06 Feb 2014 10:26:32 Local

Analysis complete: 06 Feb 2014 11:33:40 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real_time seconds

Observation start time: 30 Jan 2014 06:06:33 LITC

Data directory: R:\Observation Records\A14CO

Observatory\TWB\Gage CS1220\20140130 Io-A-C\2014-01-30 45 CH01\Folder.00001

Number of digitized input files: 153

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 153 input files, including padding: 292536

DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

FFT sweeps per digitized data burst including dead time padding: 1912

First input filename: AS CH01-001.sig

FFT sweeps per digitized data burst: 1023

Last input filename: AS CH01-153.sig Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz

FFT bins: 2048 FFT sweep time: 204.8 μ s

Digitized burst cycle time: 392 ms

Digitized burst file duration: 209.696 ms Dead time between data bursts: 182,304 ms.

Digitization coverage: 53.4939 percent

FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574)

SPS output file name: AJ4CO-TWB-20140130060633.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Jan 2014 06:06:33.999 UTC SPS file end time: 30 Jan 2014 06:07:33.911 UTC

FFT display high frequency: 4.8 MHz (FFT bin # 984) Total FFT bins exported to SPS file: 411

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset per FFT element zero: 11.3699 μ W (last FFT sweep of last data file)