TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 09 Feb 2014 02:54:01 Local Analysis complete: 09 Feb 2014 04:02:21 Local

Data Conversion Analysis Report

Observation start time: 30 Jan 2014 06:14:20 UTC Duration of observation: 59.976 real-time seconds

Data directory: R:\Observation Records\A14CO Observatory\TWB\Gage CS1220\20140130 Io-A-C\2014-01-30 51 CH01\Folder.00001 Number of digitized input files: 153 First input filename: AS CH01-001.sig Last input filename: AS CH01-153.sig Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53,4939 percent FFT bins: 2048 FFT sweep time: 204.8 μ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

 $\label{eq:FFT BW: 5 MHz} FFT BW: 4.88281 \ \text{kHz} FFT RBW: 4.88281 \ \text{kHz} FFT Windowing: None (uniform window)} \\ FFT display low frequency: 2.8 \ \text{MHz} (FFT bin \pm 574) \\ FFT display high frequency: 4.8 \ \text{MHz} (FFT bin \pm 984) \\ Total FFT bins exported to SPS file: 411 \\ \\ DC offset per FFT element zero: 11.1527 \ \mu\text{W} (last FFT sweep of last data file) \\ DC offset applied to FFT before calculating dBm: 100 \ \mu\text{W} \\ DC offset applied to FFT after calculating dBm: 11 \ \text{dBm} \\ SPS file detector sensitivity: 50 \ \text{ADC counts per dB} \\ DC offset applied to SPS data before export to SPS file: 1000 \ \text{ADC counts} \\ \\$

SPS output file name: AJ4CO–TWB–20140130061420.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Jan 2014 06:14:20.000 UTC SPS file end time: 30 Jan 2014 06:15:19.911 UTC