TWB Gage Signal File to RSS SPS File Converter Analysis run date: 12 Feb 2014 00:49:56 Local

Data Conversion Analysis Report

Analysis complete: 12 Feb 2014 01:56:42 Local

Duration of observation: 59,976 real_time seconds

Observation start time: 30 Jan 2014 06:34:34 LITC

Data directory: R:\Observation Records\A14CO

Observatory\TWB\Gage CS1220\20140130 Io-A-C\2014-01-30 64 CH01\Folder.00001

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 153 input files, including padding: 292536

DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

FFT sweeps per digitized data burst including dead time padding: 1912

Number of digitized input files: 153

First input filename: AS CH01-001.sig Last input filename: AS CH01-153.sig

Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms

FFT bins: 2048

Dead time between data bursts: 182,304 ms. Digitization coverage: 53.4939 percent FFT sweep time: 204.8 μ s

FFT sweeps per digitized data burst: 1023

FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window)

SPS output file name: AJ4CO-TWB-20140130063434.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 30 Jan 2014 06:34:34.999 UTC SPS file end time: 30 Jan 2014 06:35:34,911 UTC

FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

SPS file detector sensitivity: 50 ADC counts per dB

DC offset per FFT element zero: 11.1439 μ W (last FFT sweep of last data file)

DC offset applied to FFT before calculating dBm: 100 μ W