TWB Gage Signal File to RSS SPS File Converter Analysis run date: 26 Feb 2014 21:19:51 Local

Analysis complete: 26 Feb 2014 22:28:48 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real_time seconds

Observation start time: 31 Jan 2014 06:39:24 LITC

Data directory: R:\Observation Records\A14CO

Observatory\TWB\Gage CS1220\20140131 Io-B\2014-01-31 15 CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS CH01-001.sig

Last input filename: AS CH01-153.sig Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms

Dead time between data bursts: 182,304 ms. Digitization coverage: 53.4939 percent FFT bins: 2048

FFT sweep time: 204.8 μ s FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

> FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin \sharp 574) FFT display high frequency: 4.8 MHz (FFT bin # 984)

DC offset applied to FFT after calculating dBm: 11 dBm

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 12.4963 μ W (last FFT sweep of last data file)

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to FFT before calculating dBm: 100 μ W

SPS output file name: AJ4CO-TWB-20140131063924.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 31 Jan 2014 06:39:24.000 UTC SPS file end time: 31 Jan 2014 06:40:23,911 UTC