TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 21 Mar 2014 01:57:30 Local Analysis complete: 21 Mar 2014 03:02:30 Local

## **Data Conversion Analysis Report**

Duration of observation: 59,976 real\_time seconds

Observation start time: 10 Mar 2014 02:40:44 LITC

Data directory: R:\Observation Records\A14CO

Observatory\TWB\Gage CS1220\20140310 Io-C\2014-03-10 03 CH01\Folder.00001

Number of digitized input files: 153

First input filename: AS CH01-001.sig

Total FFT bins exported to SPS file: 411

Last input filename: AS CH01-153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms Dead time between data bursts: 182,304 ms. Digitization coverage: 53.4939 percent

FFT bins: 2048

FFT sweep time: 204.8  $\mu$ s

FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536 FFT BW: 5 MHz

FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz ( FFT bin # 574 ) FFT display high frequency: 4.8 MHz (FFT bin # 984)

SPS output file name: AJ4CO-TWB-20140310024044.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 10 Mar 2014 02:40:44.999 UTC SPS file end time: 10 Mar 2014 02:41:44.911 UTC

DC offset per FFT element zero: 10.044  $\mu$ W (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100  $\mu$ W DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB DC offset applied to SPS data before export to SPS file: 1000 ADC counts