TWB Gage Signal File to RSS SPS File Converter Analysis run date: 23 Mar 2014 00:34:22 Local

Analysis complete: 23 Mar 2014 01:41:10 Local

Data Conversion Analysis Report

Duration of observation: 59,976 real_time seconds

Observation start time: 11 Mar 2014 03:45:14 LITC

Data directory: R:\Observation Records\A14CO Observatory\TWB\Gage CS1220\20140311 Io-B\2014-03-11 10 CH01\Folder,00001

Number of digitized input files: 153

Digitized burst cycle time: 392 ms

FFT sweeps per digitized data burst: 1023

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

Dead FFT sweeps between each digitized data burst: 889

Total FFT sweeps for 153 input files, including padding: 292536

FFT sweeps per digitized data burst including dead time padding: 1912

First input filename: AS CH01-001.sig

Last input filename: AS CH01-153.sig

FFT bins: 2048 FFT sweep time: 204.8 μ s

Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

Digitized burst file size: 2096961 samples per file

Dead time between data bursts: 182,304 ms. Digitization coverage: 53.4939 percent

FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984) DC offset per FFT element zero: 10.9715 μ W (last FFT sweep of last data file)

SPS output file name: AJ4CO-TWB-20140311034514.sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 11 Mar 2014 03:45:14.999 UTC SPS file end time: 11 Mar 2014 03:46:14.911 UTC

DC offset applied to FFT before calculating dBm: 100 μ W DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

Total FFT bins exported to SPS file: 411

FFT BW: 5 MHz