

TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 27 Sep 2014 02:06:53 Local

Analysis complete: 27 Sep 2014 02:08:46 Local

Data Conversion Analysis Report

Observation start time: 26 Sep 2014 15:13:29 UTC

Duration of observation: 1.568 real-time seconds

Data directory: R:\Observation Records\AJ4CO

Observatory\TWB\Gage CS1220\2014 09 26 Test\2014-09-26_20-44-02_CH01\Folder.00001

Number of digitized input files: 4

First input filename: AS_CH01-1.sig

Last input filename: AS_CH01-4.sig

Digitized burst file size: 2096961 samples per file

Digitized burst file sample rate: 10 MHz

Digitized burst file duration: 209.696 ms

Digitized burst cycle time: 392 ms

Dead time between data bursts: 182.304 ms

Digitization coverage: 53.4939 percent

FFT bins: 2048

FFT sweep time: 204.8 μ s

FFT sweeps per digitized data burst: 1023

Dead FFT sweeps between each digitized data burst: 889

FFT sweeps per digitized data burst including dead time padding: 1912

Total FFT sweeps for 4 input files, including padding: 7648

FFT BW: 5 MHz

FFT RBW: 4.88281 kHz

FFT Windowing: None (uniform window)

FFT display low frequency: 2.8 MHz (FFT bin # 574)

FFT display high frequency: 4.8 MHz (FFT bin # 984)

Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 15.6345 μ W (last FFT sweep of last data file)

DC offset applied to FFT before calculating dBm: 100 μ W

DC offset applied to FFT after calculating dBm: 11 dBm

SPS file detector sensitivity: 50 ADC counts per dB

DC offset applied to SPS data before export to SPS file: 1000 ADC counts

SPS output file name: AJ4CO-TWB-20140926151329.sps

SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second

SPS file start time: 26 Sep 2014 15:13:29.000 UTC

SPS file end time: 26 Sep 2014 15:13:30.566 UTC