TWB Gage Signal File to RSS SPS File Converter

Analysis run date: 29 Jan 2015 18:43:26 Local Analysis complete: 29 Jan 2015 20:01:01 Local

Data Conversion Analysis Report

Observation start time: 26 Jan 2015 07:40:22 UTC Duration of observation: 59.976 real-time seconds

Data directory: V:\Observation Records\2015 01 26 Io-A-C\2015-01-26_20_CH01\Folder.00001

Number of digitized input files: 153 First input filename: AS_CH01–001.sig Last input filename: AS_CH01–153.sig

Digitized burst file size: 2096961 samples per file Digitized burst file sample rate: 10 MHz Digitized burst file duration: 209.696 ms Digitized burst cycle time: 392 ms Dead time between data bursts: 182.304 ms Digitization coverage: 53.4939 percent

FFT bins: 2048 FFT sweep time: 204.8 µs FFT sweeps per digitized data burst: 1023 Dead FFT sweeps between each digitized data burst: 889 FFT sweeps per digitized data burst including dead time padding: 1912 Total FFT sweeps for 153 input files, including padding: 292536

> FFT BW: 5 MHz FFT RBW: 4.88281 kHz FFT Windowing: None (uniform window) FFT display low frequency: 2.8 MHz (FFT bin # 574) FFT display high frequency: 4.8 MHz (FFT bin # 984) Total FFT bins exported to SPS file: 411

DC offset per FFT element zero: 15.2675 µW (last FFT sweep of last data file) DC offset applied to FFT before calculating dBm: 100 µW DC offset applied to FFT after calculating dBm: 11 dBm SPS file detector sensitivity: 50 ADC counts per dB DC offset applied to SPS data before export to SPS file: 1000 ADC counts

> SPS output file name: V:\Observation Records\2015 01 26 Io-A-C\AJ4CO TWB 2015 01 26 - 020 - 07 40 22 .sps SPS data file sweep rate: 4882.81 sweeps (FFT spectra) per second SPS file start time: 26 Jan 2015 07:40:22.000 UTC SPS file end time: 26 Jan 2015 07:41:21.911 UTC